



e EverServ[®]
7200



Where **Elegance** and **Power** meet.



Advanced Design, Proven Reliability

Selecting the right POS hardware for your business is an important decision that impacts the level of service you provide your guests for many years. While your business requires a POS system that is super rugged and has the reliability you can count on, you don't want a POS terminal that detracts from your company's image. Now you can have a POS terminal with the best of both worlds – elegant AND durable!

The totally redesigned PAR EverServ 7000 family of POS hardware is built with the same rugged durability PAR is known for but in an innovative, sleek design that delivers the performance you need.

The EverServ 7200 is built to perform in harsh environments that involve rough treatment and liquid spills. The sleek, contemporary design of the 7200 makes it the perfect choice for image conscious operators. The high performance next-gen architecture of the 7200 supports demanding applications and delivers the speed you need to improve customer throughput.

Benefits



Proven Reliability

High Quality Standards – Designed and built with the high standards for rugged durability PAR is known for.

Stable Base – Low center of gravity design is built to withstand vibration without impacting performance.

Spill Proof – Built to operate even when liquids are poured on the terminal.

Enhanced Image

Sleek Design – Clean lines and contemporary look enhances the customers' and store associates' perception of the company. The optional low-profile configuration eliminates traditional bulky hardware between the server and the customer and maximizes social interaction for improved customer service.



Superior Serviceability

I/O Centralization – Fully centralized I/O port connectivity makes it easier to manage cables, upgrade components and provide connectivity for multiple configurations.

Easy Access – Major components such as storage (HD or SSD) and memory are easy to access for simplified replacement and increased uptime. Some components can be accessed through the side of the unit without removing cables.



Increased Revenues

Customer Displays – Optional customer displays (2 lines x 20 character Vacuum Fluorescent Display (VFD) or 5"x7" static display or 12" customer display) enhance up-sell and cross-sell opportunities which increase revenues.

Low Total Cost of Ownership

Advanced Power Management – Advanced energy saving features and auto-standby mode dramatically reduces overall power consumption.



Powering Better Guest
Experiences[™]



PAR EverServ® 7200 Details

Operating System

Windows Embedded POSReady 7
 Windows 7 Professional for
 Embedded Systems
 Windows 7 Professional

PC BIOS & Hard Disk

AMI BIOS APTIO EFI and SMBIOS
 2.5" SATA, 320 GB¹

Processor & Memory

Processor

Intel® Atom™ D2550 1.86 GHz dual core (Cedar Trail Architecture)

Memory

4 GB DDR3-SODIMM (laptop style)

Environmental Information

Operating Environment

Temperature: 41 to 104° F (5 to 40° C)
 Relative Humidity: 10-90% (Non-condensing)

Transit Environment

Temperature: 0 to 158° F (-18 to 70° C)
 Relative Humidity: 5-95% (Non-condensing)

Size & Weight

Height: 15.7 inches (40.0 cm)
 Width: 15.1 inches (38.4 cm)
 Depth: 10.6 inches (26.9 cm)
 Weight: 25.5 lbs. (11.6 kg)

Note: The dimensions and weight above are based on a typical system configuration. The dimensions and weight may vary depending on the position and angle of the main LCD display and if optional features are attached to the POS terminal.

¹ 1 GB means 1 billion bytes; actual capacity varies with preloaded material and operating environment will be less.



Touch Screen

15" 5-Wire Resistive




Flexible Configurations



Wall Mounted



Ceiling Mounted



Low Profile

PAR EverServ® 7200 Details



LAN & Power Supply

LAN
10/100/1000 Mbit Ethernet

Power Supply
19V/150W External Power Brick

Customer Display Options



Standard



5x7" Card Holder



2x20 VFD Display

Ports & Expansions

- LED stacked indicators - HDD, PWR
- 1 – 12V power output jack 2A
- 1 – PWR Conn input 19V
- 1 – USB 2.0 24V powered
- 4 – USB ver. 2.0
- 1 – DVI-I – Video out, supporting both DVI and VGA monitors
- 2 – RJ12 Cash drawer ports
- 5 – COM ports:
 - 2 – COMs (RJ45)
 - 2 – COMs (RJ45) selectable for +5v or +12v
 - 1 – COM Circular DIN for serial customer display options
- 1 – RJ45 LAN 10/100/1000Mbit
- 1 – Power on/off switch
- 1 – PS/2 interconnect



Options

- Second 320 GB Hard Disk Drive
- Solid State Drive
- International (256x64) Double Byte Display
- Wireless
- Bluetooth
- Biometrics
- Dallas Key

Certifications

cULus, FCC Class A, RoHS
WEEE, CB (IEC), CE, CCC
BSMI, C-Tick/RCM,
IRAM/S-MARK, KC, SASO
KUCAS, VCCI, PSE



Powering Better Guest
Experiences™